

# DP-8510

## Modular Banknote Sorter

Expandable up to 16 pockets with  
a 13-inch touch screen



The DP-8510 sorts mixed banknotes by **denomination, fitness and orientation** with fewer steps and higher speed. It detects unfit notes — soiled, folded, taped, torn or with holes — and recognizes up to **32 currencies** simultaneously. Expandable up to **16 sorting pockets** plus reject pocket, with individual configuration per pocket, a **13" touch screen** and a built-in cleaning system for intensive use with low maintenance.

### Features

- Sorts by denomination, fitness and orientation
- 1,000 notes/min at high speed
- Detects soiled, folded, torn or taped notes
- Recognizes up to 32 currencies simultaneously
- Expandable up to 16 pockets + reject
- Individual configuration per pocket
- Built-in cleaning system
- 13" touch screen
- 1,000-note tray
- 600 notes per stacker
- 300-note reject pocket
- Detection by CIS, magnetic, infrared and UV
- LAN, RS232, USB and external display interface
- Optional serial number scanning

A



Front view

B



Feeder module

# Technical Specifications

| Specification         | Detail                                                                   |
|-----------------------|--------------------------------------------------------------------------|
| Sorting modes         | Count, Mix, Sort, Face, Orientation,<br>Fitness, Emission                |
| Sorting speed         | 1,000 / 900 / 750 notes/min                                              |
| Counterfeit detection | CIS, magnetic, infrared, ultraviolet                                     |
| Currencies            | ARS, USD, EUR (up to 32 simultaneous)                                    |
| Capacity              | 1,000 notes (tray)<br>600 notes per stacker<br>300 notes (reject pocket) |
| Maximum pockets       | Up to 16                                                                 |
| Display               | 13" touch screen                                                         |
| Interface             | LAN, RS232, USB, external display                                        |
| Dimensions            | Approx. 715 × 1,043 × 380 mm                                             |
| Net weight            | Approx. 80 kg                                                            |
| Optional              | Serial number scanning                                                   |
| Power supply          | AC 100-240 V, 50/60 Hz                                                   |
| Consumption           | 200 W maximum                                                            |

